



MITSUBOSHI

Cable for elevator

Product name : EVV-L

RoHS2

JIS C3408

Application

Our cables for elevator (EVV-L) are a lift cable that uses a voltage of less than 300V.

For example: dumbwaiter
(elevator for small parcels)

Features

For the insulator, a soft vinyl chloride mixture with excellent tensile properties and oil resistance is used, and for the sheath, a super-flexible vinyl chloride with excellent flexibility is used, resulting in a cable that is easy to handle with excellent flexibility.



Dimension table

Number of core × size	Conductor construction	Conductor outside diameter mm	Core outside diameter mm	Sheath thickness mm	Finish outside diameter mm	Weight kg/km	Conductor resistance 20°C Ω/km	Allowable current A
2×0.75mm ²	(A) 30/0.18	1.1	1.9	1.0	6.0	55	25.6	11
3×0.75mm ²				1.0	6.3	65		9
4×0.75mm ²				1.0	6.8	75		8
6×0.75mm ²				1.1	8.1	95		7
8×0.75mm ²				1.1	9.3	130		7
10×0.75mm ²				1.2	10.7	165		6
12×0.75mm ²				1.2	11.8	195		6
20×0.75mm ²				1.2	12.4	295		5

Office Information

If you have any questions or requests, please contact us.



MITSUBOSHI CO.,LTD Electric Wire Division

Osaka Branch TEL 06-6261-8884(代) FAX 06-6261-5550

Tokyo Branch TEL 03-6897-8660(代) FAX 03-6897-8665

Kyushu Sales Office TEL 092-526-2615(代) FAX 092-526-2781

Nagoya Sales Office TEL 052-760-4636(代) FAX 052-760-4637

Shiga Factory TEL 0748-86-6104(代) FAX 0748-86-2103

URL : <http://www.kk-mitsuboshi.co.jp/>